



SEM SYSTEM Pensile e Basamento



solo su richiesta, per sostituzioni o ricambi.
viene rimpiazzato dai modelli CHE 50-75-120-200



System SS
Senza Scambiatore



System I
Integrativo



SP 65



SB 75



SB 100



SB 120

CODICE		20201	20211	20301	20311	20401	20411	20501	20511
TIPO	um	SP - 65 SS	SP - 65 I	SB - 75 SS	SB - 75 I	SB - 100 SS	SB - 100 I	SB - 120 SS	SB - 120 I
Altezza	mm	900	900	1000	1000	800	800	1100	1100
Larghezza	mm	580	580	450	450	550	550	550	550
Profondità	mm	450	450	450	450	550	550	550	550
Capacità boiler	m ³	65	65	75	75	74	74	120	120
Capacità totale	lt	121	121	136	136	170	170	235	235
Capacità circuito primario	lt	56	47	61	52	96	90	115	102
Capacità circuito secondario	lt	-	7	-	8	-	5	-	10
Superficie scambiatore	m ²	-	2	-	2,3	-	1,8	-	2,8
Perdita di carico circuito primario	mm.c.a.	100	200	100	200	100	200	100	100
Perdita di carico circuito secondario	mm.c.a.	-	1.600	-	1.700	-	1.400	-	2.200
Scambio con 10° Dt	Kcal/h	-	16.000	-	18.000	-	14.000	-	22.000
Attacchi circuito primario	G "	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4
Attacchi circuito secondario	G "	1"	3/4	1"	3/4	1"	3/4	1"	3/4
Attacchi sanitario	G"	1/2	1/2	1/2	3/4	3/4	3/4	3/4	3/4
Max press.eserc.sanitario	ate	6	6	6	6	6	6	6	6
Max.press.eserc.secondario	ate	6	6	6	6	6	6	6	6
Potenza resistenza elettrica	W	1200	1200	1200	1200	1200	1200	1200	1200
Tensione di alimentazione	V	220	220	220	220	220	220	220	220
Peso con imballo	Kg	91	117	69	86	69	83	108	128